

TACO

PERFORM 300 XL

Tersedia di:



QHOMEMART

JL. RAYA JANTI NO.96 YOGYAKARTA
(0274) 493 22 88 , 08112863773 (CHAT ONLY)
f qhomemart t qhomemart @ qhomemart qhomemart
WWW.QHOMEMART.COM

STONE SERIES

Wear Layer **0.2mm**
Thickness **3.0mm**

Size **457.2mm x 914.4mm**
8 pieces/box **3.34sqm**



TV 3040 XL
Canada Beige



TV 3041 XL
Texas Grey



TV 3042 XL
Colorado Nero



TV 3043 XL
Austin Linston



TV 3044 XL
Houston Linston



TV 3045 XL
Dallas Linston



WOOD SERIES

Wear Layer **0.2mm**
Thickness **3.0mm**

Size **228.6mm x 1219.2mm**
12 pieces/box **3.34sqm**



TV 3034 XL Alaska Park



TV 3035 XL Oslo Sand



TV 3036 XL Malibu Beach

WOOD SERIES

Wear Layer **0.2mm**
Thickness **3.0mm**

Size **228.6mm x 1219.2mm**
12 pieces/box **3.34sqm**



TV 3037 XL Jeju Alley



TV 3038 XL Padang Bay



TV 3039 XL Havana Land

TECHNICAL DATA

CHARACTERISTICS	TEST METHOD	PASS
Resistance to chemicals	EN423:93 Class 0	✓
Bearing castor	EN425:94	✓
Dimension squareness and straightness	EN427:94	✓
Thickness overall	EN429:93	✓
Thickness wear layer	EN429:93	✓
Residual indentation after static load	EN433:94	✓
Dimensional stability and curling after exposure to heat	EN434:94	✓
Shrinkage rate	≤0.25%	✓
Curling	≤2mm	✓
Flexibility	EN435:94(A) Bend around 20mm mandrel shows no sign of cracking	✓
Abrasion resistance	EN660-1/-2	✓
Color fastness to light	EN 20 ISO 105-B02 6 or above	✓
Toxic element test	EN 71-3	✓
Specific gravity	ASTM D792:91	✓
Coefficients of friction	ASTM D1894:01	✓
Sound reduction	DIN52210:4db	✓
Flammability	EN 71-2	✓
Smoke density	DIN4102/ASTM D2843-99:Class B1	✓
Electrical resistance	EN1081 Method C	✓
Fungus test	ASTM G21:96 Grade 1	✓
IMO resolution	MSC61(67) Part 2 MSC61(67) Part 5	✓ ✓

PRODUCED UNDER HIGH QUALITY SUPERVISION WITH ISO 9001 ISO 14001 OHSAS 18001 CE STDS.



100%
WATERPROOF



EASY TO CLEAN &
MAINTAIN



TERMITE
PROOF



SIMPLE & QUICK
TO INSTALL

Wood Series



Stone Series

